

# HTL3200UV UV Roll-to-Roll Inkjet Printer Series



\*Illustration purpose

## Optional Models:

- **HT1800UV** Extremely cost-effective RTR printing solution
- **HTH3200Turbo** High-precision synchronous single and dual roll printing solution
- **HTL3200UV** Professional wide-format RTR printing solution
- **HT5000UV** 5-meter super-wide RTR printing solution

**Range of Large Format Printers with high speed drop on demand piezo inkjet technology. Outstanding Performance:**



- Automatic Negative Pressure System
- 0-30mm Automatic Height Measurement
- Automatic Width Measurement System
- Adjustable UV Curing Power
- High Precision Components
- Mesh Cloth Printing Function (optional)
- Dual Roll Feeding System (HTH3200Turbo & HT5000UV)
- Supports Multi-Roll Material Printing (HT5000UV)







- Water-Cooled Printing Platform & Adjustable Suction Area (HTH3200Turbo & HTL3200UV & HT5000UV)
- Water-Cooled LED Light
- Automatic Ink Control System with Solenoid Valve
- Multi-Point Pneumatic Fabric Pressure Device
- Sensitive Anti - collision Device
- Positioning Rod
- Optional Anti-Static Bar
- High-Quality Imported Components

# UV Roll-to-Roll Inkjet Printer Series

Model	HT1800UV	HTH3200Turbo	HTL3200UV	HT5000UV	
<b>Printing Information</b>					
Printhead	GEN6		Kyocera		
Number of Printhead	2-8 Pcs	4-12 Pcs	2-4 Pcs	4-12 Pcs	
Resolution	605*1800 DPI		363*3600 DPI		
Production Mode	Draft	65 m <sup>2</sup> /h	156 m <sup>2</sup> /h	74 m <sup>2</sup> /h	192 m <sup>2</sup> /h
	Production	56 m <sup>2</sup> /h	115 m <sup>2</sup> /h	56 m <sup>2</sup> /h	140 m <sup>2</sup> /h
	Quality	41m <sup>2</sup> /h	82 m <sup>2</sup> /h	45 m <sup>2</sup> /h	95 m <sup>2</sup> /h
Print Mode	Bi-directional high speed				
<b>Media   Ink</b>					
Max. Print Width	1.8 m	3.2 m	3.2 m	5.0 m	
Max. Media Thickness	2 mm				
Media Type	Light sheets, soft films, car stickers, printed fabrics, light box fabrics, non-woven fabrics, elastic fabrics, wallpaper, and wall coverings, among others.				
Ink	Environmentally friendly UV / LED curable ink (VOC free)				
Ink Color	CMYK、Lc、Lm、V、W	CMYK、Lc、Lm、W		CMYK、Lc、Lm、V、W	
<b>Features</b>					
UV Curing	LED				
Interface	USB				
RIP Support	Caldera / Onyx (Optional Purchase)				
Image Format	PDF, JPEG, TIFF, EPS, AI, etc.				
<b>Dimension   Weight</b>					
Printer Size(L*W*H)	4.51*0.96*1.33 m	5.98*1.85*1.90 m	6.46*1.31*1.71 m	8.88*2.03*2.02 m	
Printer Net Weight	1200 KG	2800 KG	1800 KG	6300 KG	
Printer Gross Weight	1500 KG	3600 KG	2550 KG	8170 KG	
<b>Power Supply   Environment</b>					
Power Consumption	4 kW (19A)	8.7 kW (38A)	3.9 kW (18A)	11.1 kW (25A)	
Power Supply	220VAC 50Hz 3L/N/PE	230VAC 50Hz 3L/N/PE	230VAC 50Hz 3L/N/PE	400VAC 50Hz 3P/N/PE	
Environment	Separate workroom in cleaning and ventilated condition, avoid direct sunlight. Temperature:18-30°C(64-86 °F) Constant Humidity:30-70% (non-condensing)				
Others	Requires ADP / Computer				

## Industrial Digital Inkjet Printing Solution Provider

<p>Independent printhead-drive technology</p> 	<p>Self-developed control system</p> 	<p>Self-developed MES system</p> 	<p>Independent ink industrial chain</p> 	<p>Remote service maintenance system and local services</p> 
---	--	--	---	---



### Shenzhen HandTop Tech Co.,Ltd

**Add:** No.39 Qingfeng Road, Baolong Street, Longgang District, Shenzhen  
(2-3/F, Building C, Jingmida Digital Culture Industry Park - HanGlory Group)  
**Tel:** +86 0755-23080896 / 23062862 **E-mail:** info@hanglorygroup.com  
**Fax:** +86 0755-23217841 **Web:** www.hanglorygroup.com/en

© The above information is for reference only. Shenzhen HandTop Tech Co.,Ltd. reserves the right of final interpretation. Descriptions, illustrations and specifications here of are subject to change without prior notice. Final details shall be subject to contract signed.

V3.0/2025